



G168 v1.1

Design for Fatigue

Revision

Rev.	Author	Revised	Released	Date	Notes
Draft	D. Malcolm			2017-2-6	
Review	A. Ojeda			2017-2-6	
Final	K. Wolf			2017-2-6	

Scope

This document describes the methodology used in the design of Wind Harvest International's G168 turbine for fatigue loads. It presents in detail the results of the process for some of the critical components including the mast-to-shaft connection, the drive shaft, the blades, and the blade at the connection to the middle arm.

Contents

1	Introduction	4
2	Methodology	5
3	Mast connections	6
3.1	SN curve for welded flange	7
3.2	Fatigue life prediction for mast-shaft connection	8
4	Drive shaft.....	9
4.1	Material properties.....	10
4.2	Fatigue life prediction.....	11
5	Blade bending	12
5.1	Reinforcement of the blade at upper and lower arm connections	12
5.2	Material properties of blade	13
5.2.1	Fatigue strength from [12] Strength of Aluminum, Alcan, 1968.	13
5.2.2	Fatigue strength from Ref. [13], CSA S157.1	14
5.3	Fatigue damage from normal operation	15
5.4	Fatigue damage from starts and stops.....	15
6	Middle arm-central mast connection	17
6.1	Bolt slippage.....	18
6.2	Normal operating conditions	18
6.3	Start-stop cycles	19
7	References.....	20

Figures

Figure 1.	General arrangement of G168 with direct drive generator.....	4
Figure 2	Procedure for fatigue strength design.....	5
Figure 3.	End of mast tube with welded flange.....	6
Figure 4.	SN curves for steel details from Eurocode 3, 1993	7
Figure 5.	Fatigue strength categories for butt welds from Eurocode 3, 1993	8
Figure 6.	Upper end of drive shaft.....	9
Figure 7.	SN curve for 1040 steel from ref. [9]	10
Figure 8.	SN curves for 1040 steel from ref. [10]	10
Figure 9.	Approximate distribution of flap- and edge-wise blade bending.....	12

Figure 10. Blade reinforcement at the upper and lower arm connections12

Figure 11. Fatigue strength of bolted aluminum, from Ref. [12]13

Figure 12. Joints qualifying as Category B fatigue strength, from Ref. [13]14

Figure 13. Fatigue strength of aluminum categories, from Ref [13]14

Figure 14. Connection between middle arm and central mast17

Tables

Table 1. Bending loads and fatigue damage at mast-shaft connection 9

Table 2. Idealized SN curve for drive shaft used in LIFE75 calculations11

Table 3. Bending loads and fatigue damage on drive-shaft, upper bearing11

Table 4. Geometric blade properties with and without reinforcement13

Table 5. Fatigue strength of bolted connection, R=0.5, 6351-T6, from [12]14

Table 6. Bending loads and fatigue damage at upper arm-blade connection.....15

Table 7. Estimate of fatigue damage due to start-stop cycles.....16

Table 8. Loads at connection due to normal operation with stop.....18

Table 9. Fatigue damage under normal operation at middle arm-mast connection19

Table 10. Stresses in connection due to start-stop cycles19